

OUR FINISHES: SUMMARY TABLE

General note: the resistance of our finishing products is suitable for everyday use in a home, but their long-term durability depends on strict compliance with the technical data sheets when implementing the products and the maintenance that will be carried out subsequently.

Discover our new demonstration videos on www.mercadier.fr!

PROJECT ->	Bathroom sink unit	Shower Floor	Shower Walls	Kitchen worktop / splashback	Decorative wall	Floors in living rooms (living room, dining room, bedroom)	Kitchen floor	Grand Passage floor (including public floors)	Outside	ASSOCIATED CONCRETE	METHOD	ASPECTS	
IMPREGNATOR						iodii. sediodiii				EBC PMB	IMPRENGATOR: 1 to 3 coats spaced 1 to 4 hours apart	SEMI MATTE TO SATIN DEPENDING ON THE NUMBER OF COATS	
AQUA MAT IMPREGNATOR + PROTECTOR										ЕВС РМВ	IMPREGNATOR: 2 to 3 coats spaced 1 to 4 hours apart PROTECTIVE: 2 to 3 coats spaced 2 to 8 hours apart depending on temperature	MAST	
SOLVENT-BASED IMPREGNATOR + COLORLESS PROTECTOR								Caution: strong odor		ЕВС РМВ	temperature IMPREGNATOR: 2 to 3 coats spaced 1 to 4 hours apart PROTECTIVE: 2 to 3 coats spaced 2 to 8 hours apart depending on temperature IMPREGNATOR: 2	SATIN	
IMPREGNATOR + TWO- COMPONENT SOLVENT-BASED VARNISH TO DILUTE										EBC PMB	to 3 coats spaced 1 to 4 hours apart TWO- COMPONENT SOLVENT-BASED VARNISH 2 coats spaced 12 hours	SEMI-MATTE / SATIN	
IMPREGNATOR + BI-AQUA VARNISH							In 3 layers	In 3 layers		EBC PMB SC+ AXXX	anart IMPRENGATOR: 2 to 3 coats spaced 1 to 4 hours apart BI- AQUA VARNISH: 2 to 3 coats in the same day spaced at least 2 hours apart		
<u>Legend</u>								CAUTION: Before applying the protections, the concrete must have a residual humidity of less					
	Adapted								than 1% and a support temperature of more than 10/12°C.				
Not suitable													
			MERCADIER	- 120 rue Emilien (Lenfant – 13290 Ai	ix en Provence - S	Siren 480 184 928					

Version 06/03/2025