

MAINTENANCE PROTOCOL

EBC / PMB SC+ / RBX / AXXX cast floors

Guarantees of good performance and longevity can only be acquired when using the complete system from the Mercadier range (primer, 'concrete' and finish).

The concretes used may be:

Colored Concrete Coating – Pure Mineral Concrete

SC+

RBX

AXXX

Compliance with these technical data sheets during application (temperature, precise dosage of mixtures, application conditions, etc.) and the maintenance required for the finished product will determine its appearance, resistance and longevity.

In particular, the quantities of finishing products consumed will be very important in terms of the stain resistance of the products. The porosity of the product can depend in particular on the application conditions. A PU varnish film, for example, applied to a support not previously saturated/sealed with our impregnator, or applied in too thin a thickness may not resist stains, without however compromising its effectiveness.

Regardless of the finish chosen, regular maintenance is necessary. The frequency will vary depending on the use of the space and the finish selected.

ROUTINE MAINTENANCE

Action	Frequency	Products/Means	Method
Routine maintenance	Daily	- <i>Dusting</i> : Damp mop - <i>Cleaning</i> : “Cleansing Shampoo” diluted according to FT - <i>Tasks</i>	- <i>Dusting</i> : Remove dust and loose dirt by wiping the floor with a well-wrung damp mop - <i>Manual or mechanical wet cleaning</i> *: remove stubborn dirt, ideally with diluted Mercadier shampoo (according to FT) by cleaning the floor by damp wiping with a mop or using a scrubber-dryer* - Apply the “Stain Remover” from the Mercadier range according to the Technical Data Sheets.

REFRESHMENT

Action	Frequency	Products/Means	Method
Refreshment	Depending on attendance and conditions of use	- <i>Cleaner + scrubber dryer</i> * "Shampoo Cleaner » diluted according to FT - "Metallizing"	- Before refreshing the floor, clean the surface a little more intensively to completely remove dirt using the scrubber-dryer*. Rinse well. Allow to dry. - Apply a layer of "Metallizer" using a moistener

*The scrubber dryer must have rubber wheels and must be equipped with the softest brush possible.

RENOVATION

Action	Frequency	Products/Means	Method
Renovation	Depending on attendance and conditions of use	- "Intensive Shampoo before renovation » from the Mercadier range + black PAD single-brush - PU varnish	- Carry out an intensive cleaning of the surface with a diluted superactive stripper using a single-brush machine to remove all dirt. Rinse well. Let dry. - Apply the PU Varnish in 2 coats on the completely dry floor using a roller, following the technical data sheet. The floor will be usable for pedestrian traffic the next day, but the varnish will not harden for another 10 days. Please ensure that you follow the specific points set out below during this time.

PREVENTIVE MEASURES ON NEW FLOOR (FOR 10 DAYS)

The PU Varnish system reaches its core hardness after 10 days, during this period:

- Avoid traffic .
- Do not cover during.
- Do not install carpets.
- Do not wet, dry clean for about ten days.

GENERAL PREVENTIVE MEASURES

Much of the common dirt can be avoided by installing brush mats in entrances. These must have a minimum size of 2 to 3 steps.

Chairs and tables not fitted with felt glides and chairs with unsuitable casters, which destroy the surface, should be avoided.

Attach felt pads to the underside of furniture legs that are likely to be moved regularly.

Do not allow colored water and stains to stagnate .

Remove stains immediately, as some types of stains become embedded in the coating, making them difficult or even impossible to remove.

Avoid using bleach and ammonia-based products during daily maintenance, which could leave darker or yellow marks on the coating.

The use of high-pressure cleaners, steam cleaners or any other aggressive cleaning equipment is prohibited.