

ACRYLIC STUCCO

FEATURES

Odorless, low-VOC finishing stucco for interiors and exteriors based on acrylic copolymer in aqueous dispersion. It provides a smooth, very shiny stuccoed appearance, very aesthetically pleasing using the STUCCO SPATOLATO ALLA VENEZIANA technique.

We recommend using **ACRYLIC STUCCO** to achieve strong, saturated colors.

IMPLEMENTATION

- Preparation of supports

The supports and their preparation will comply with the rules of the art and the DTU in force (clean, dry, non-friable and free from salts, humidity and mold).

The substrates must be smooth and homogeneous in absorption, therefore unprepared substrates (plasterboard, plasterboard, fiber cement, siporex, wood, old paint, fillings, grooves and other similar substrates) must be leveled or raked then fixed with a water-based primer.

INSTRUCTIONS FOR USE

- Applicable in pre-tinted system only indoors according to our color charts "L'Ame En Couleur" of 68 colors and "20ans" of 17 colors. Mix well before application.

Ready to use, applied with a stucco trowel (ITALIAN TRAPEZOIDAL TROWELS) in 3 coats. Can be applied in only 2 coats. Dry and recoatable after approximately 4-6 hours.

Apply a first coat to cover the base. Rake in a thin layer as best as possible. Allow to dry, then sand if necessary with 100 or 120 grit sandpaper.

Second rake to "zero" to obtain the smoothest possible appearance. Let dry, then sand if necessary with fine sandpaper type n° 320 or 400.

Finish with a third pass, more or less butterflying using the stucco trowel to obtain the stucco effect and ironing as you go before drying to obtain the shiny appearance.

It is possible to layer several colors or to apply them alternately during the last layer.

For better protection and a more radiant effect, finish with the application of **SOLID WAX**.

Avoid applying **ACRYLIC STUCCO** on hot surfaces and/or surfaces directly exposed to the sun, on windy days, on damp surfaces or in the rain.

Consumption: approximately 0.7 kg/m² for 3 coats

RECOMMENDATIONS

In case of contact with eyes, rinse thoroughly with fresh water and consult a doctor if symptoms persist. Keep out of reach of children.

CLEANING AND PRESERVATION

Clean tools with water. Apply and store at temperatures between 5°C and 35°C. Store for 1 year in its original sealed packaging in a dry, frost-free place.

Packaging of 5 kg and 20 kg.

The information contained in this sheet is the expression of our knowledge and test results; it cannot under any circumstances be considered as providing a guarantee or as engaging our liability in the event of defective application.