

ECO IMPRESSION

PRODUCT DESCRIPTION

ECO IMPRESSION is a low-VOC, water-based, matte white primer for interiors.

It is easily applied to different types of new and old supports and allows the supports to be consolidated and homogenized before the application of our MATECO[®] paint.

PROPERTIES

- Very good covering power
- High vapor permeability
- Does not block the support from breathing, prevents blisters and peeling due to humidity.
- Great ease of application

AREAS OF APPLICATION

- Coatings
- Plaster
- Cardboard plasterboards
- Plaster tiles
- Cement-based support
- Old water-based paints
- Wood and derivatives

SURFACE PREPARATION

Don't neglect surface preparation. This is an essential step for a perfect finish and to ensure its longevity.

The supports must be prepared in accordance with DTU 59.1. to which is added the following specific preparation: the bases must be sound, dry, coherent and suitable for the application.

ECO IMPRESSION is applied to porous surfaces such as coatings, plasters and derivatives.

Old supports, such as old paints, blocked backgrounds, must be cleaned and sanded before applying the print.

Plaster and plaster derivatives

Allow the plaster to dry for at least 30 days. Remove all excess plaster and other foreign matter.

Concrete, cement, brick

Before painting, remove all roughness, dirt and dust.

Old paintings

Scrape and brush to remove any loose parts of the surface.

Fill, smooth and sand if necessary.

Overly porous or powdery supports:

Apply a foundation fixer

Other support: Contact us

IMPLEMENTATION

Follow the recommendations for surface preparation before starting to paint.

ECO IMPRESSION must be diluted with 10% water. A greater dilution may be possible depending on the porosity of the substrate. Mix well before application.

ECO PRINTING is applied with a roller or brush.

Theoretical yield : 6 to 7 m²/l for an undiluted product

Drying time :

Dust-free: 1 to 2 hours

Recoverable: min 3 hours

Complete drying: 24 hours depending on temperature

Implementation temperature: from +5°C to +30°C

hot or damp surfaces.

Protect neighboring areas from possible projections.

CLEANING

Rinse hands and tools immediately with soap and water after use.

STORAGE

Storage: Store in a dry place and in its original unopened packaging: maximum 12 months.

SAFETY AND PRECAUTION

Refer to the product Safety Data Sheet.

Exposure limit value according to Directive No. 2004/42/EC: Class A/a: 30g/L.

This product, ready to use, contains a maximum of 30/L of VOCs (*)

(*) Volatile Organic Compounds



In accordance with the new French regulations that impose limit values for the VOC (Volatile Organic Compound) content of construction products, this Mercadier product is environmentally friendly. This regulation requires that construction and decoration products have a label indicating their volatile pollutant (VOC) emission level in a simple and legible manner.

*Information on the level of emission of volatile substances in indoor air, presenting a risk of toxicity by inhalation, on a class scale ranging from A+ (very low emissions) to C (high emissions).

The information contained in this sheet is the expression of our knowledge and test results; it cannot under any circumstances be considered as providing a guarantee or as engaging our liability in the event of defective application.