

FIXATIVE

FEATURES

Odorless, low-VOC adhesive for indoor and outdoor use based on vinyl acetate copolymers, modified acrylic polymers and retarders in aqueous dispersion.

FIXATIVE improves the characteristics of mixtures based on lime, cement, plaster, etc. , by regulating and modifying hardening times while increasing mechanical resistance and adhesion, which considerably improves application.

In restoration, **FIXATIVE** is indicated to improve the various types of mixtures used for stone restoration. In the restoration of plasters, it is used as an adhesive on cracks.

It is also suitable for making a bonding slip for paint and lime finishing plasters to be applied to old surfaces or with cement repairs or cement surfaces.

INSTRUCTIONS FOR USE

Ready to use, mix well before use.

For lime plasters: approximately 3 to 6% of the weight of the binder or in combination with ADDITIVE approximately 150g of each for 25kg of plaster.

For lime paints: approximately 5 to 10% of the binder weight.

To fill cracks: approximately 2 to 6% of the weight of the binder in combination with STUC POUDRE for example.

For high-strength cement coatings: approximately 4 to 6% of the binder weight.

To delay the setting of the plaster: approximately 2 to 6% of the weight of the binder.

To make a bonding slip: approximately 1 volume of **FIXATIVE** and lime to 8 volumes of water.

Avoid applying this product to hot surfaces and/or surfaces directly exposed to the sun, on windy days or in the rain.

RECOMMENDATIONS

In case of contact with eyes, rinse thoroughly with fresh water and consult a doctor if symptoms persist.
Keep out of reach of children.

CLEANING AND PRESERVATION

Clean tools with water. Apply and store at temperatures between 5°C and 35°C. Store for 1 year in its original sealed packaging in a dry, frost-free place.

Packaging of 1 kg and 10 kg.

test results ; it cannot under any circumstances be considered as providing a guarantee or engaging our liability in the event of defective application.