

MATECO®

PRODUCT DESCRIPTION

MATECO® is a low-VOC water-based decorative paint for interiors.

MATECO® elegantly decorates, renovates and protects your walls and ceilings, while preserving the initial structure of the support and allowing it to breathe.

MATECO® is easy to apply to various types of old and new surfaces. It is very economical and has a high yield thanks to its excellent filling power. MATECO® is high quality and odorless, and is highly decorative. Its dry appearance creates a smooth, mineral-matte film similar to limewash.

It is available in 21 colors, however custom colors can be produced on request and under certain conditions.

PROPERTIES

- Very good covering and opacifying power.

Rich in mineral fillers: calcium carbonate and titanium oxide.

Deep matte appearance.

High vapor permeability.

Does not block the support from breathing, prevents blisters and peeling due to humidity.

Very easy to apply.

AREAS OF APPLICATION

Living room walls and ceilings.

APPLICATION SUPPORT

Coating

Plaster

Cardboard plasterboards

Plaster tiles

Cement-based supports

Old water-based paints

Wood and derivatives

SURFACE PREPARATION

Don't neglect surface preparation. This is an essential step for perfect application of your finishing paint and to ensure its longevity.

The substrates must be prepared in accordance with DTU 59.1. The substrates must be sound, dry, consistent and suitable for application, free of all non-adherent parts.

Porous supports such as coatings, plasters and derivatives must be primed beforehand with a layer of our ECO IMPRESSION printing.

Old supports, such as old paints, blocked backgrounds, will have to be cleaned, and sanded then primed if necessary with our ECO IMPRESSION printing.

SURFACE PREPARATION

Follow surface preparation recommendations before painting.

MATECO® paint must be diluted with 5% to 10% water. Greater dilution may be possible depending on the porosity of the substrate. Mix well before application.

MATECO® Apply with a roller or brush (like a lime wash), in two coats.

Theoretical yield

10 m² / L / layer or 5m²/L for 2 layers.

Drying time

Dust-free: 1 to 2 hours

Recoverable: min. 3 hours

Complete drying: 24 hours depending on temperature

Operating temperature: From +5°C to +30°C

Do not use on hot or humid surfaces. Protect surrounding areas from possible splashes.

CLEANING

Clean tools with water immediately after use.

STORAGE

Keep for 1 year in its original, full, well-closed packaging, away from frost and high heat.

IMPLEMENTATION

Refer to the product Safety Data Sheet.

Exposure limit value according to Directive No. 2004/42/EC: Class A/ α : 30g/L.

This product, ready to use, contains a maximum of 14/L of VOCs (*)

(*) Volatile Organic Compounds



In accordance with the new French regulations that impose limit values for the VOC (Volatile Organic Compound) content of construction products, this Mercadier product is environmentally friendly. This regulation requires that construction and decoration products have a label indicating their volatile pollutant (VOC) emission level in a simple and legible manner.

* Information on the level of emission of volatile substances in indoor air, presenting a risk of toxicity by inhalation, on a class scale ranging from A+ (very low emissions) to C (high emissions).

The information contained in this sheet is the expression of our knowledge and test results; it cannot under any circumstances be considered as providing a guarantee or as engaging our liability in the event of defective application.