

# METALLISING

## PRODUCT DESCRIPTION

---

High-quality water-based care emulsion. Ready to use, this metallizer is used for the maintenance and renovation of our varnished concrete.

It forms a resistant film with an antistatic effect limiting the adhesion of dirt.

It enhances the appearance of the surface while extending the life of the floor.

- Matte appearance
- Solvent-free
- Wear resistant
- Quick drying
- Easy to use

## AREAS OF APPLICATION

---

- Interior
- Soils

## NECESSARY TOOLS

---

Mop or wet broom, bucket.

Vacuum cleaner.

Protective gloves/goggles.

## PREPARATION OF THE SUPPORT

---

Dust off.

Clean the surface: damp cleaning with Cleaning Shampoo or Intensive Cleaning depending on the dirtiness of the surface to be treated (see FT).

Dry the surface thoroughly.

## PREPARATION OF THE MIXTURE

---

Shake the can well before use.

**For protective care/first maintenance:**

10ml/m<sup>2</sup> of pure Repairing Metallizer.

**For routine maintenance:**

Dilute 150ml in 5l of water.

## IMPLEMENTATION

---

The ideal conditions are: 18 to 25°C with an air humidity between 35% and 65%

Using a moistener, apply a thin layer, spreading and pulling the product always in the same direction.

Do not create puddles or excess water.

Let dry.

## FINAL DRYING / RETURN TO SERVICE

---

Dry to the touch: approximately 30 min depending on weather conditions (mentioned above).

Wait 1 hour for complete drying and possible use.

On the other hand, wait 1 day before replacing carpets or other floor coverings and heavy objects.

## ROUTINE MAINTENANCE / RENOVATION

---

After applying the metallizer, use the shampoo for routine maintenance.

To preserve the product and its finish (varnish, wax, etc.), it is recommended to attach felt pads to the feet of furniture, chairs, etc., even if they are made of plastic. Do not let stains of colored water or grease remain for too long. Wipe them up as quickly as possible. Use standard, non-aggressive products to clean surfaces.

Absolutely avoid ammonia-based products and high-dose anti-limescale products.

It is important to maintain the surface by regularly applying a coat of the final finishing product (after cleaning if necessary and light sanding to restore good adhesion).

The frequency of this operation depends on the use made of it (check if water 'beads' on the support).

## YIELD & PACKAGING & STORAGE

---

Packaging: 750ml and 5L bottles.

Yield: 5 repairs maximum for floors ~15 m<sup>2</sup>

Shelf life: 2 years.

## RECOMMENDATIONS AND WARNINGS

---

Consult the most recent version of this technical sheet ([www.mercadier.fr](http://www.mercadier.fr)). Our Sales department has Distance and our resellers are at your disposal for any further information.

The guarantees of good performance and longevity of the product can only be acquired in the event of strict compliance with the instructions for use of the product itself, but also those of any primers and finishing products as well as the maintenance recommendations. We cannot therefore be held liable in any way in the event of an application not in accordance with our information and not using our entire system.

The information, tips and advice relating to the end use of MERCADIER products are provided in good faith. They are based on the knowledge and experience that MERCADIER has acquired to date with its products when properly stored, handled and applied under normal conditions. In practice, differences between materials, substrates and specific site conditions are such that this information or any written recommendations or advice given do not imply any warranty of merchantability other than the legal warranty against hidden defects.

## SAFETY AND PRECAUTION

---

Components: according to regulation (EC) No. 648/2004: contains <5% non-ionic surfactants, perfumes.  
Safety data sheet available on request.

Cleaning tools: immediately with water after use.

Close the opened bottle immediately.

Store for 2 years in the original, unopened bottle at temperatures between 5°C and 30°C. Protect from frost.

Keep locked up and out of reach of children.



In accordance with the new French regulations that impose limit values for the VOC (Volatile Organic Compound) content of construction products, this Mercadier product is environmentally friendly. This regulation requires that construction and decoration products have a label indicating their volatile pollutant (VOC) emission level in a simple and legible manner.

As this product has not yet been tested, it is classified C pending the results, but this does not mean that it is "harmful."

\*Information on the level of emission of volatile substances in indoor air, presenting a risk of toxicity by inhalation, on a class scale ranging from A+ (very low emissions) to C (high emissions).

The information contained in this sheet is the expression of our knowledge and test results; it cannot under any circumstances be considered as providing a guarantee or as engaging our liability in the event of defective application.